

 Facet[®]

DURA-LIFT[®]

Solid State Electronic Fuel Pump





WE MOVE FUEL®

Facet® Dura-Lift® fuel pumps are respected by both the OE and Aftermarket for their proven quality performance and dependability in thousands of diesel transfer applications.

In tough, hard working applications ranging from truck refrigeration units... to marine generator sets... to diesel filtration systems... to industrial applications and other diesel or gasoline lift applications these Dura-Lift fuel pumps have “earned the right” to carry the Facet brand.

- Self-priming to 120 inches dry lift
- 33 gal/hr
- 9 to 15 psi...specifications vary by model
- 4 hour dry run
- Available in 12 or 24 volt model
- State of the art electronics
- Sealed electronics
- Self-regulating pressure
- VCA approved EC95/54
- 80 micron stainless steel filter
- Transient protection
- Reverse polarity protection
- Available with internal stainless steel components
- Light-Weight: 3 lbs at 7 1/4 inches
- Corrosion resistant over 100 hours salt spray
- Easy 2 bolt mounting
- Transparent fuel filter bowl allows filter monitoring
- Low power requirements 1.4 amp on average
- Internal check valve
- ELV compliant
- Ground positive or negative
- Compatible with gasoline, diesel, biodiesel, E85, blended alcohol and fuel additives
- Operating temperature range -40° F to +180° F



FACET®/PUROLATOR® BRANDED FUEL PUMPS ARE MANUFACTURED BY MOTOR COMPONENTS LLC AN ISO9001-2008 FACILITY FOR DESIGN AND ENGINEERING INFORMATION CONTACT: PAUL PULEO, NATIONAL SALES MANAGER Phone: 607-737-8371 FAX: 607-737-8335 p.puleo@facet-pruolator.com MOTOR COMPONENTS LLC ELMIRA, NEW YORK 14903 www.facet-pruolator.com © Registered Trademark of MOTOR COMPONENTS LLC